



Kömmerling®

TODAY FOR TOMORROW



INDIVIDUAL. SAFE. HIGH-QUALITY.

**Kömmerling 88 residential door
Standard**

SUSTAINABLE, SAFE AND COMPLETELY TO YOUR TASTE

Kömmerling 88 residential door Standard

With the Kömmerling 88 centre seal residential door system, you give your guests a warm welcome – and uninvited guests a bitter disappointment thanks to intelligent burglary protection measures. The residential door with a installation depth of 88 mm is not only characterised by high security, but also by excellent thermal insulation, outstanding weather tightness, optimal statics – and last but not least by a wide range of design options.

SECURE

- High burglary protection up to resistance class RC 2 (MC 2)
- Additional protection against driving rain thanks to aluminium weather bars and specially designed sealing blocks near the rebate
- Trend-setting six-chamber design with steel reinforcement of maximum dimensions and welded corner connector for improved static properties
- Threshold connector for an accurate fit and sealing between the frame and threshold
- Deep glazing rebate for modern triple glazing, special functional glazing or residential door panelling up to 58 mm



SUSTAINABLE

- Highly insulating residential door system with centre seal and a installation depth of 88 mm
- High weather tightness thanks to double sealing to the barrier-free residential door threshold with thermal break
- Optimal protection against cold and heat
- Significant reduction of CO₂ emissions as well as high energy and cost savings

ADAPTABLE

- Inward or outward opening residential doors
- In addition to classic white, it is also available in many plain, metallic and woodgrain colors as well as with the premium coating proCoverTec
- Variety of functional/ornamental glazing, residential door panelling and additional fittings
- Maximum sash sizes of
single-sash residential door:
1200 x 2400 mm
double-sash residential door:
1000 x 2400 mm



#KömmerlingForTomorrow